

nēta

Rotor Rain™

Mini Sprinklers

Features & Benefits

- Low trajectory with large drops
- C frame design for strength and high distribution uniformity
- Colour-coded nozzles for flow rate identification
- Full flow spinner suspended between two bearings for reliable performance
- Break-off spray deflector for close-in watering: ideal for immature trees
- Applications include vine crops, bananas and tree crops including citrus and apples
- Independently tested by the Australian Irrigation Technology Centre, report No. A9010



PERFORMANCE		TESTED 0.2m ABOVE GROUND			
NOZZLE COLOUR AND ORIFICE SIZE	PRESSURE (kPa)	FLOW (lph)	DIAMETER OF THROW (m)	HEIGHT STREAM (m)	DEFLECT OR DIAMETER (m)
GREEN 1.5 mm	100	77	7.8	0.54	2.8
	150	94	8.7	0.54	
	200	110	9.1	0.64	
	250	120	8.5	0.66	
BLUE 1.7 mm	100	100	8.6	0.66	2.8
	150	125	9.3	0.74	
	200	145	9.6	0.77	
	250	163	9.3	0.88	
YELLOW 2.0 mm	100	147	10.0	0.62	3.0
	150	183	11.0	0.80	
	200	215	11.2	0.94	
	250	240	11.0	0.99	
RED 2.4 mm	100	195	11.0	0.64	3.2
	150	240	12.5	0.89	
	200	280	12.5	0.99	
	250	315	12.1	1.05	
PURPLE 2.8 mm	100	265	11.2	0.79	4.0
	150	330	12.8	0.92	
	200	385	13.0	1.06	
	250	430	12.4	1.12	



Specifications:

Dimensions Assembled	Rotor Rain™ 3/8"	Rotor Rain™ 1/2"	UV Stabilised Material	Base/Connection Type
Height	49mm	49mm	Frame - Acetal	Inlet: Thread 3/8" BSP M
Width	46mm	46mm	Flipper - Nylon	
Weight (approx)	8.0g	10.5g	Nozzle - Acetal	



General Sales Enquiries
 P: 1300 771 134
 F: 1800 332 555
sales@netaindustries.com.au
www.netagarden.com.au